Product data sheet



W600 REAR MODULAR DEVICE RAIL PRISMA G



03004

! Discontinued on: 23/03/2023

① Discontinued

Main

Range	Prisma	
Range Of Product	Prisma G	
Product Or Component Type	Rail	
Accessory / Separate Part Category	Installation accessory	
Range Compatibility	Prisma Prisma G	
Type Of Rail	Modular Rear	
Installed Device	Altistart: ATS01N103/106FT TeSys: fixed D or K contactors <= 40 A - horizontal installation TeSys: fixed GV2 + D or K contactors <= 40 A - horizontal installation TeSys: fixed GV3Pxx1 + LC1D40 to D65 - horizontal installation TeSys: fixed TeSys U - horizontal installation	
Poles Description	9 x 4P: fixed D or K contactors <= 40 A horizontal installation 9 x 3P: fixed GV2 + D or K contactors <= 40 A horizontal installation 7 x 3P: fixed GV3Pxx1 + LC1D40 to D65 horizontal installation 9 x 3P: fixed TeSys U horizontal installation	

Complementary

Installation Description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm
	Pack enclosure - width 555 mm
	- dok one occur - make occur -
Number Of Vertical Modules [50	4 module(s): ATS01N103/106FT in 600 mm Widefloor-standing enclosure
Mm]	4 module(s): ATS01N103/106FT in 600 mm Widewall-mounted enclosure
	4 module(s): ATS01N103/106FT in 555 mm WidePack enclosure
	3 module(s): D or K contactors <= 40 A, direct in 600 mm Widefloor-standing
	enclosure
	3 module(s): D or K contactors <= 40 A, direct in 600 mm Widewall-mounted
	enclosure
	3 module(s): D or K contactors <= 40 A, direct in 555 mm WidePack enclosure
	5 module(s): GV2 + D or K contactors <= 40 A, direct in 600 mm Widefloor-standing
	enclosure
	5 module(s): GV2 + D or K contactors <= 40 A, direct in 600 mm Widewall-mounted
	enclosure
	5 module(s): GV2 + D or K contactors <= 40 A, direct in 555 mm WidePack
	enclosure
	7 module(s): GV3Pxx1 + LC1D40 to D65, direct in 600 mm Widefloor-standing
	enclosure
	7 module(s): GV3Pxx1 + LC1D40 to D65, direct in 600 mm Widewall-mounted
	enclosure
	7 module(s): GV3Pxx1 + LC1D40 to D65, direct in 555 mm WidePack enclosure
	5 module(s): TeSys U, direct in 600 mm Widefloor-standing enclosure
	5 module(s): TeSys U, direct in 600 mm Widewall-mounted enclosure
	5 module(s): TeSys U, direct in 555 mm WidePack enclosure
	4 module(s): TeSys U, direct in 600 mm Widefloor-standing enclosure
	4 module(s): TeSys U, direct in 600 mm Widewall-mounted enclosure
	4 module(s): TeSys U, direct in 555 mm WidePack enclosure

9 Mm Pitches

Quantity Per Set	Set of 1	
Height	35 mm	
Width	465 mm	
Depth	16 mm	
Net Weight	0.16 kg	
Colour	Natural	
Material	Metal	

Environment

Standards	IEC 61439-1 IEC 61439-2	
Product Certifications	ASEFA	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.5 cm
Package 1 Width	3.5 cm
Package 1 Length	47 cm
Package 1 Weight	160 g



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc
⊘	Toxic Heavy Metal Free
⊘	Mercury Free
②	Rohs Exemption Information Yes
Ø	Halogen Free Plastic Parts Product

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile