
Product data sheet

Specifications

SGreen Premium"



LINERGY FC DISTRIBUTION BLOCK FOR COMPACT NSX250 3P TOGGLE/ FIXED+CONNECTION

04403

(!) Discontinued

() Discontinued on: 18/09/2023

Main

Range	Linergy	
Range Of Product	Linergy	
Product Or Component Type	Device feeder	
Product Name	Linergy FC	
Accessory / Separate Part Category	Connection accessory	
Range Compatibility	Prisma Prisma P cubicle	
Provided Equipment	Prefabricated flexible connection to Linergy busbars	

Complementary

Installation Description	Cubicle - width 650 mm
Number Of Devices	4 (3P)
Poles Description	3P
Installed Device	ComPact: fixed NSX100160 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX100160 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: toggle - vertical installation ComPact: fixed INS250 - control: direct front rotary handle - vertical installation ComPact: fixed INV250 - control: direct front rotary handle - vertical installation
Mounting Support	Mounting plate
Installation Direction	Horizontal
[Ui] Rated Insulation Voltage	750 V AC
[Uimp] Rated Impulse Withstand Voltage	8 KV
[le] Rated Operational Current	800 A at 40 °C
[Ue] Rated Operational Voltage	690 V
[lpk] Rated Peak Withstand Current	50 kA
I ² T On Activation	25000000 A².s
Permissible Current	800 A at 40 °C 725 A at 60 °C 675 A at 70 °C
Connections - Terminals	Supply: flexible bars (phase) , 32 x 8 mm Outgoer: plug in (phase) , 4 outgoers

Standards	IEC 61439-1 IEC 61439-2
Product Certifications	KEMA ASEFA
Quantity Per Set	Set of 1
Length	440 mm
Height	132 mm
Depth	235 mm
Net Weight	6 kg
Colour	Black

Packing Units

-	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	15.0 cm
Package 1 Width	24.0 cm
Package 1 Length	45.5 cm
Package 1 Weight	5.96 kg
Unit Type Of Package 2	P12
Number Of Units In Package 2	35
Package 2 Height	90.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	220.6 kg

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information