# Product data sheet

Specifications





### TeSys F contactor - 4P (4 NO) -AC-1 - <= 440 V 1000 A - coil 220 V DC

LC1F6304MD

① Discontinued

#### Main

Range	TeSys
Range Of Product	TeSys F
Product Or Component Type	Contactor
Device Short Name	LC1F
Contactor Application	Resistive load
Utilisation Category	AC-1
Poles Description	4P
[Ue] Rated Operational Voltage	<= 1000 V AC 50/60 Hz <= 460 V DC
[Uc] Control Circuit Voltage	220 V DC
[le] Rated Operational Current	1000 A (at <40 °C) at <= 440 V AC AC-1

#### Complementary

[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	1000 A (at 40 °C) 1250 A
Rated Breaking Capacity	5040 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	5050 A 40 °C - 10 s 4400 A 40 °C - 30 s 3400 A 40 °C - 1 min 2200 A 40 °C - 3 min 1600 A 40 °C - 10 min
Associated Fuse Rating	1000 A gG at <= 440 V 630 A aM at <= 440 V
Average Impedance	0.12 mOhm - Ith 1000 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V conforming to IEC 60947-4-1 1500 V conforming to VDE 0110 group C
Power Dissipation Per Pole	120 W AC-1
Overvoltage Category	III
Power Pole Contact Composition	4 NO
Control Circuit Voltage Limits	Operational: 0.851.1 Uc (at 55 °C) Drop-out: 0.20.35 Uc (at 55 °C)
Mechanical Durability	5 Mcycles
Inrush Power In W	1600 W (at 20 °C)

Life Is On Schneider

Hold-In Power Consumption In W	0.W/ at 20.°C
	9 W at 20 °C
Maximum Operating Rate	1200 cyc/h 55 °C
Operating Time	6070 ms closing
	4050 ms opening
Connections - Terminals	Control circuit: screw clamp terminals 1 cable(s) 14 mm <sup>2</sup> flexible without cable end
	Control circuit: screw clamp terminals 2 cable(s) 14 mm²flexible without cable end
	Control circuit: screw clamp terminals 1 cable(s) 14 mm <sup>2</sup> flexible with cable end
	Control circuit: screw clamp terminals 2 cable(s) 12.5 mm <sup>2</sup> flexible with cable end
	Control circuit: screw clamp terminals 1 cable(s) 14 mm <sup>2</sup> solid without cable end
	Control circuit: screw clamp terminals 2 cable(s) 14 mm <sup>2</sup> solid without cable end
	Power circuit: bar 2 cable(s) - busbar cross section: 60 x 5 mm
	Power circuit: bolted connection
Tightening Torque	Control circuit: 1.2 N.m
	Power circuit: 58 N.m
Mounting Support	Plate
Heat Dissipation	9 W
Standards	IEC 60947-4-1
	JIS C8201-4-1
	IEC 60947-1
	EN 60947-4-1
	EN 60947-1
Product Certifications	CCC
	LROS (Lloyds register of shipping)
	DNV
	ABS
	CB
	BV
	RINA
	RMRoS
	UL
Compatibility Code	LC1F

### Environment

Ip Degree Of Protection	IP20 front face with shrouds conforming to IEC 60529 IP20 front face with shrouds conforming to VDE 0106
Protective Treatment	тн
Ambient Air Temperature For Operation	-555 °C
Ambient Air Temperature For Storage	-6080 °C
Permissible Ambient Air Temperature Around The Device	-4070 °C
Height	304 mm
Width	389 mm
Depth	255 mm
Operating Altitude	3000 m without derating
Net Weight	21.5 kg

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

## **Contractual warranty**

Warranty

### Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free

Rohs Exemption Information Yes

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins